



## SFP to Ethernet Switch SDT-4SFP-2GE

This SFP to Ethernet Switch makes transmission between UTP Copper cables and Slot SFP (Small Form-Factor Plug-gable) transceivers. It is designed to meet the massive needs for Ethernet network deployment and able to extend a copper based network via Slot cable to a maximum distance up to 120km. It can be installed into a Standard Converter Chassis. The installation & operation procedures are simple & straight forward. Operation status can be locally monitored through a set of Diagnostic LED located in the front panel.

### *Features*

- \* In conformity to IEEE802.3 10base-T, IEEE802.3u 100 base-TX/FX, IEEE802.3ab 1000 base-T, IEEE802.3z, 1000base-SX/LX, IEEE802.1a, IEEE802.1PQ0S, IEEE802.1d Spanning Tree.
- \* Hot Pluggable & Wall-Mountable.
- \* Stable performance more than 50 thousand hours with fault-free.
- \* Unique IC solution applied.
- \* Supports 10/100Mbps and 10/100/1000M full/half duplex, easy upgrades.
- \* Optional function: VLAN 802.1Q
- \* Auto MDI/MDI-X.
- \* Auto Negotiation.
- \* Support flow control.
- \* Stable performance more than 50 thousand hours with fault-free.
- \* Interface: RJ-45 connector / SFP Slot
- \* In conformity with safety code of FCC, CE and RoHS.

## Specifications

Optical Interface (SFP)	Connector	SFP LC/SC
	Data Rate	100Mbps, 1000Mbps
	Duplex Mode	Full duplex
	Slot	MM 50/125um,62.5/125um SM 9/125um
	Distance	100Mbps: MM 550M/2km,SM 20/40/60/80/100/120km 1000Mbps: MM 550m/2km,SM 20/40/60/80/100/120/140km
	Wavelength	MM 850nm,1310nm SM 1310nm,1550nm WDM Tx1310/Rx1550nm(A side),Tx1550/Rx1310nm(B side) WDM Tx1490/Rx1550nm(A side),Tx1550/Rx1490nm(B side)
UTP Interface	Connector	RJ45 Port
	Data Rate	10/100Mbps, 10/100/1000Mbps
	Duplex Mode	Half/full duplex
	Cable	Cat5,Cat6
Power Input	Adapter Type	DC5V
	Power Built-in Type	AC100~240V
Power Consumption		<3W
Temperature		0~50°C Operating; -40~70°C Storage
Humidity		5~95%(no condensing)
MTBF		≥10.0000h
Certification		CE,FCC,RoHS

## Application

- \* Extend your Ethernet connection up to 0~120km away using Slot optics
- \* Creates an economical Ethernet-Slot/copper-Slot link for connecting remote sub-networks to larger Slot optic networks/backbones
- \* Converts Ethernet to Slot, Slot to copper/Ethernet, ensuring optimum network scalability for connecting two or more Ethernet network nodes (e.g. connecting two buildings on the same campus)
- \* Designed to provide high-speed bandwidth for demanding large scale work groups that require expansion of Gigabit Ethernet Network.